

GHG444



組合: 6 個配件

GHG448



組合: 18 個配件

GHG449



組合: 36 個配件

GHG447



組合: 54 個配件

- ▶ Ex II 2 G Ex de ia/ib m IIC T6
- ▶ 防水防塵等級: IP66

- ▶ 材質: Glass-fiber Reinforced polyester
- ▶ 工研院認證: 工電(2015)第 00333 號

可選配以下防爆配件:

 <p>防爆押扣開關 1NO+1NC</p> <ul style="list-style-type: none"> ▶ Ex II 2 G Ex de IIC/IIB Gb ▶ 防水防塵等級: IP66 ▶ 電流/電壓: 16A, 500VAC 	 <p>防爆 ON/OFF 押扣開關 1NO+1NC</p> <ul style="list-style-type: none"> ▶ Ex II 2 G Ex de IIC/IIB Gb ▶ 防水防塵等級: IP66 ▶ 電流/電壓: 16A, 500VAC
 <p>防爆緊急停止開關</p> <ul style="list-style-type: none"> ▶ Ex II 2 G Ex de IIC/IIB Gb ▶ 防水防塵等級: IP66 ▶ 電流/電壓: 16A, 500VAC 	 <p>防爆兩段選擇開關</p> <ul style="list-style-type: none"> ▶ Ex II 2 G Ex de IIC/IIB Gb ▶ 防水防塵等級: IP66 ▶ 電流/電壓: 16A, 500VAC ▶ 可選用左、右復歸
 <p>防爆三段選擇開關</p> <ul style="list-style-type: none"> ▶ Ex II 2 G Ex de IIC/IIB Gb ▶ 防水防塵等級: IP66 ▶ 電流/電壓: 16A, 500VAC ▶ 可選用左、右復歸 	 <p>防爆電阻計</p> <ul style="list-style-type: none"> ▶ Ex II 2 G Ex de IIC/IIB Gb ▶ 防水防塵等級: IP66 ▶ 瓦數/電壓: 1W, 250VAC ▶ 0-10,000 Ohm
 <p>防爆指示燈</p> <ul style="list-style-type: none"> ▶ Ex II 2 G Ex de IIC/IIB Gb ▶ 防水防塵等級: IP66 ▶ 電壓: 20V-254 V AC/DC ▶ 可選用顏色: 白, 黃, 紅, 藍, 綠色 	 <p>防爆電流表 AM72</p> <ul style="list-style-type: none"> ▶ Ex II 2 G Ex e II ▶ 防水防塵等級: IP66 ▶ 測量電流: 0-600/900A