

## 整流器系列 AC→DC

Rectifiers			DC output voltage						Page
			12	24	48	60	110	220	
Type designation	AC input	Output power W (max.)	DC output current (@ nom. voltage)						
Version									
PSR06-W	1 x 230V <sub>AC</sub>	600		20.0	10.0	8.2	4.5		22
Wall cabinet									
PSR308 WIR	90-270V <sub>AC</sub>	800 600*		30.0 (25.0*)	16.7 (12.5*)	13.5 (10.0*)	7.5 (5.5*)	3.7 (2.7*)	23
19" unit									
V750C**	90-264V <sub>AC</sub>	840	60.0					27	
19" unit									
PSR312	1 x 230V <sub>AC</sub>	1200		50.0				26	
19" unit									
PSS18	1 x 230V <sub>AC</sub>	1800		40.0	30.0	25.0	13.3	6.7	24
19" unit									
Flatpack2 2000**	85-290V <sub>AC</sub>	2000		84.0				25	
19" unit									
PSR327	1 x 230V <sub>AC</sub>	2700			56.0	45.0	25.0	12.5	28
19" unit									
PSR380	3 x 400V <sub>AC</sub>	8000					74.0	37.0	29
19" unit									

\*在 120VAC 下

在工業和電信電源系統應用方面，Eltek Valere Industrial 生產了各種模組化整流器。所有裝置都配有適用於插槽的 19" 滑入式結構。對於底板連接，帶後端連接器的模組配有內建 decoupling device 和輸入、輸出保險絲。使用 Can Bus 介面可與中央監控系統 UPC3 或 UPC3S(\*\*Smartpack) 進行快速、安全的通信。此外，內建充電處理器可確保所有通用電池單獨作業。



敦川企業有限公司

Tel: (02)2729-7727 • Fax: (02)2729-1127

Email: sunlux@ms14.hinet.net